



**Gfp** **Graphic Finishing**  
partners

**Where Finishing Comes First.**

## **Gfp 865DH-4RS**

### **Versatile Dual Heat Laminator**

For finishing professionals who need versatility, quality, and economy in one machine, the Gfp 865DH-4RS delivers. Turn out thermal encapsulation with low melt films (1.5-10mil), PSA lamination, and mounting jobs quickly and easily.

#### **ULTIMATE FLEXIBILITY**

*Dual heat for thermal & cold apps*

#### **MAXIMIZE PRODUCTIVITY**

*Inline Rotary Slitters*

#### **FAST ROLL CHANGES**

*Front/Rear Swing-out shafts* **EASY**

#### **LOADING**

*3" Quick-Grip Swing-out Shafts*

#### **INDUSTRIAL DESIGN**

*Years of maintenance-free service*



***laminating • mounting • encapsulating***

***Our most flexible, cost-effective laminator yet***

Spend less time on set-ups and changeovers with swing-out Quick-Grip supply shafts. Two front rewind shafts allow thermal encapsulation of prints from a roll.



- Labor saving swing-out supply shafts
- Drop-in Quick-Grip rewind shafts
- Photoelectric eye for operator safety
- Independent top and bottom heaters
- Web clutch adjustment for output quality
- Includes rear rewind with rotary slitters
- Swing-up feed table and 38" output height



Includes motorized rear rewind with rotary slitters for roll-to-roll applications.

Slitters not for use with thermal films.



Media Alignment disks keep supply rolls from telescoping

## 865DH-4RS

Rugged Design  
Professional Quality  
Proven Performance  
Economically Priced

### APPLICATIONS

Signs  
Posters  
POP Displays  
Trade show displays  
Dry-erase boards  
Graphic mounting  
Photo mounting  
Floor graphics  
Window graphics  
Vehicle graphics

cTUVus  
Safety  
Approval



### Warranty:

1 year parts & labor.  
Installation is included.

|   |                            |
|---|----------------------------|
| Laminating Width  | 65"                        |
| Roller Diameter   | 5"                         |
| Roller Gap  | 1"                         |
| Main rollers  | Silicone                   |
| Supply roll diameter(max)   | 16" bottom, 8" top         |
| Film shafts   | 3" aluminum Quick-Grip     |
| Rear rewind with rotary slitters<br>(Not for use with thermal films.) | Included                   |
| Max. temperature  | 266°F                      |
| Heat method   | Quartz heater              |
| Film thickness  | 1.5 - 10mil                |
| Laminating speed  | 0-13 ft/min                |
| Drive motor   | DC geared motor            |
| Pressure Adjustment   | Dual hand wheels           |
| Roller heating  | Top & Bottom               |
| Power Supply  | 240v 60HZ Single phase 24A |
| Power Consumption   | Max. 5760W                 |
| Dimensions  | 87" x 34" x 49"            |
| Net Weight w/ stand   | 846 lbs.                   |
| Shipping Dimensions (L x W x H)                                       | 90" x 40" x 63" 1129 lbs.  |

Your local dealer is:



**lloydsofindiana.com**  
**877-626-6848**

