

# Phoenix 440-ML Mounting Laminator

The Phoenix™ 440-ML Mounting Laminator was designed to be a flexible and economical resource for producing signage & display materials. The top heated roller allows for thermal product applications while the release liner rewind makes it possible to easily work with pressure sensitive materials.

## KEY FEATURES:

- ◆ Five Roller Gap Settings
- ◆ Variable Speed Control
- ◆ Variable Temperature Control
- ◆ Quick-Grip Film Shafts
- ◆ Single Knob Tension Control
- ◆ Fold Down Rear Exit Tray
- ◆ Chain Driven Rewind
- ◆ Print Roll Hangers
- ◆ Print Feed Guides
- ◆ Print Hold Down Clamp
- ◆ Emergency Stop Button
- ◆ Photoelectric Eye for Safety
- ◆ Sleep & Auto-Off Energy Saver
- ◆ Stand with Locking Casters



## APPLICATIONS

- ◆ Signs
- ◆ Posters
- ◆ POP Displays
- ◆ Trade Show Displays
- ◆ Single-sided Lamination
- ◆ Mount Graphics
- ◆ Mount Photos
- ◆ Window Graphics
- ◆ Pre-mask
- ◆ Mounting Boards
- ◆ Pouch Boards
- ◆ PSA Film

Maximum Width	44"
Roller Diameter	3.5"
Adjustable Speed	0 - 5 feet per minute
Temperature Range	100° - 302° F
Heating Method	Quartz heater
Film Weights	1.5 - 5 mil
Gap / Pressure Settings	0", 1/16", 1/8", 3/16" & 1/4"
Supply Unwind / Rewind	Quick-Grip Top
Auto Stand By	3 hours idle, drop to 176° F

Auto Sleep Function	4 hours idle, turns heat off
Tension adjustment	Single Knob
Power Supply	120v 12A
Power Consumption	1440 W
Foot Pedal / Stand	Included with unit
Dimensions, w/ rear deck up	57" L x 37.75" D x 50" H
Shipping Dimensions	59.25" L x 35.5" W x 26.75" H
Net / Shipping Weight	264 lbs. / 395 lbs.
Warranty	1-yr parts / 3 mos. labor & rollers

**LAMINATING • MOUNTING • PRE-COAT BOARDS • PRE-MASK**

**TOP ROLLER HEATED • EASY TO OPERATE • AFFORDABLE PRICE • SMALL FOOTPRINT • FLEXIBLE APPLICATIONS**