



Our one-step systems eliminate traditional "L" sealer and tunnel for manual operations
The most economical method of shrink-wrapping around the world is now available in North America

500 West Main Street, Suite 12 - Wyckoff, NJ 07481
Ph. 201.337.1001 - Fax 201.337.5001
www.shrinkfilm.com - info@shrinkfilm.com



Assembly & Testing of each system is done in-house
in our facility in Wyckoff, New Jersey

Technical data	
Sealing area	23"W x 33"L
Maximum product height	8.5"
Maximum roll width	32"
Working plate height (on stand)	36"
Impulse sealing system	Blade micro-knife
Packaging speed	Up to 360 pph
Power supply	220V, 20 Amps, 1PH
Overall machine dimensions	40"W x 75"L x 52"H
Machine weight	550 lbs.

The evolution of “one-step“ shrink wrap systems

- Each system comes with a Free Replacement Parts Kit (sealing blade, Teflon tape and rubber pad) included
- One-Step Shrink System. Shrinks and seals at the same time.
- The Q-6084 can be also used for bagging purposes (sealing only – no shrink).
- Height adjustments according to the product size.
- The slide able loading tray/film holder allows best product film sizing.
- Pin film perforator device included.
- Shrink temperature adjustment.
- The Q-6084 is equipped with casters for easy mobility.
- Only one operator required.
- Magnetic hold-down.
- Does not include end plug



For best packaging results use DYNACLEAR® shrink film

500 West Main Street, Suite 12 - Wyckoff, NJ 07481
Ph. 201.337.1001 - Fax 201.337.5001
www.shrinkfilm.com - info@shrinkfilm.com